



CSS Virtual Receiver

SG-SYSTEM 5



communicationsolutions



Features That Make a Difference

- Monitor up to 1,474,560 IP communicators (Cellular or Ethernet) with up to 24 IP line cards and upgrade License keys
- Upgradeable memory to handle extensive future IP account capacity
- Industry-leading account density per U rack for a reduced overall size of 4U
- SG-DRL5-IP line card with capacity of up to 4,096 (512 visual verification/512 supervised/3072 unsupervised) IP accounts, upgradable up to 61,440 via license keys
- Integrated redundancy eliminating downtime
- Fully 'hot swappable' modules
- Auto-switching redundancy for power and to output peripherals
- CMS access to visual verification files through SG-Systems Console
- Remote upgradable via SG-Systems Console
- Enhanced real time system status and hardware diagnostics via SG-Systems Console and touch screen interface

Making Your Investment Future-Proof

The new SG-System 5 builds upon the Sur-Gard legacy, maintaining world-leading quality standards in monitoring station receivers. Sur-Gard is known to deliver utmost reliability through features such as integrated redundancy, eliminating the costs incurred by downtime of the system. The new SG-System 5 additionally ensures that the investment in the system is future-proofed by catering to growing system requirements. Up to 1,474,560 IP Cellular or Ethernet communicators can be monitored through upgrade license keys as well as upgradeable memory.

Geared To Support Innovative Alarm Verification Solutions

The CSS SG-System 5 supports industry trending alarm verification solutions such as visual verification, significantly reducing incremental costs that can be incurred by false alarms, while adding to the security professional's RMR. PIR cameras are strategically installed as part of a security system and are activated the moment an alarm is triggered. Via the SG-System 5 Receiver, images are sent instantly through to the monitoring facility where the situation can rapidly and accurately be assessed and escalated to authorities, if required, while providing respondents with critical information. SG-System 5 allows Central Monitoring Stations access to visual verification images. In conjunction with compatible automation companies, the integrated software allows for seamless visual verification viewing and increased output that enhances the speed of processing alarm communications.

Smaller Yet Packed with Power

The lean and compact footprint of the CSS Sur-Gard System 5 virtual receiver makes space management in receiver rooms easy.

With a reduced overall size of 4U, SG-System 5 offers highest account density per U rack available in the industry.

The built-in redundancy for power and autoswitching assures continuous performance of all peripheral devices connected to the output ports. The line cards are 'hot swappable' which means they can be quickly removed and/or replaced while the system is live.

The robust CPM has built-in diagnostics that proactively identify any issues and report them to the easy-to-use Windows™-based SG-Systems Console software. Continually monitoring the automation software ensures automatic backup to a redundant port. For example, if the automation system goes offline, the CPM automatically switches from the primary Ethernet port to a secondary one, or to one of two serial ports, before going into manual mode.

Programming changes can be easily made using the menu-driven touch screen or remotely over the network Ethernet connection using SG-Systems Console Software. Firmware upgrades can be conveniently done as they become available via SG-Systems Console Software without additional hardware, eliminating associated downtime.

The SG-Systems Console Software also offers hardware diagnostics, monitoring the fan, power, network supervision as well as the overall health of System 5. An intuitive touch screen interface makes navigating through manual programming very simple. Real time system status is also available through this user-friendly touch screen.

The IP line cards – SG-DRL5-IP – support up to 512 supervised accounts, up to 512 visual verification accounts, and up to 3072 unsupervised accounts. Using license keys, two additional standard tables may be added for up to 12,228 per card. Further IP account expansion to adapt to business growth can easily be handled through SG-System 5 extended-capacity license keys with up to 15,360 unsupervised accounts, up to 2,560 supervised accounts and up to 2,560 visual verification accounts, resulting in up to 61,440 per line card and 1,474,560 for 24 lines.

Ordering Information

Main Hardware	Part No. Description
SG-S5BASE	SG-MLRF5, SG-CPM5, SG-PSU5-600 with Fan, SG-UIB5
SG-S5REDUN	SG-CPM5, SG-SG-PSU5-600 with fan, SG-UIB5
SG-DRL5-IPSTD	DRL5-IP Receiver Line Card with Paddle Board

Upgrade License Keys

Part No.	Description
SG-DRL5-IPSLIC2	Additional 512/512/3072 Visual Verification/Supervised/Unsupervised IP Accounts
SG-DRL5-IPSLIC3	Additional 512/512/3072 Visual Verification/Supervised/Unsupervised IP Accounts
SG-DRL5-IPXLIC1	Additional 1,024/1,024/6,144 Visual Verification/Supervised/Unsupervised IP Accounts
SG-DRL5-IPXLIC2	Additional 2560/2560/15,360 Visual Verification/Supervised/Unsupervised IP Accounts
SG-DRL5-IPXLIC3	Additional 2560/2560/15,360 Visual Verification/Supervised/Unsupervised IP Accounts

Spare Parts

SG-MLRF5	Sub-Rack Metal Work
SG-MLRF5-RM	Rack Mount Rails
SG-PSU5-600	600W PSU
SG-CPM5	CPM Module
SG-DRL5-IP PAD	Paddle Card
SG-S5LFANTR D	RL5-IP Line Card Fan Tray
SG-S5SERCAB	System 5 Serial Y Cables
SG-UIB5	User Interface Touch Screen Module
SG-UIB5-BP	User Interface Blank Plate

Specifications

SG-MLRF3	19" x 3.5" x 12.24" (38 cm x 9 cm x 31.1 cm) 4 U NOTE: Uses standard 19" rack 110/220 VAC, 50/60 Hz, 2.5 A (Max) 200W max.
Battery Backup	External UPS (not supplied)
Operating Environment	32 – 122 °F (0 – 50 °C) 90%, non-condensing
Built-In Connectors	- Parallel printer port - 2 X Serial RS-232 connection to Automation Software (used by monitoring station) - Serial RS-232 connection to external serial printers - Ethernet: RJ45 modular jack for 1GB or 10/100Base automation output
Line Card Capacity	Up to 24 line cards
Line Card - IP (SG-DRL5-IP)	- 512-event memory buffer/card - 128-bit AES encryption - Anti-hack design - Compatibility with all DSC IP Alarm Communicators (Cellular or Ethernet) and licensed partners - 512 Visual verification IP accounts - 512 Supervised IP accounts - 3,072 Unsupervised IP accounts
Visual Display	Touch screen user interface
Industry Approvals	
USA	- FCC Part 15 Class B - UL1610 (Commercial Burg) - UL864 (Commercial Fire) Technical Specifications - CSFM (Commercial Fire) - NIST Certification for AES 128 bit encryption
Canada	- ICES Class B - ULC-S559 (Commercial Fire) - ULC-S304 (Commercial Burg)
Europe	- CE Compliance - EN6100-6-3 - EN50130-4 - EN60950-1
Australia/New Zealand	- C-Tick Compliance

