

Meraki MX-64

100% Cloud Managed Networking and Security



communicationsolutions



Hardware

- Stateful firewall throughput: 250 Mbps
- Recommended maximum clients: 50
- Small form factor

Cloud-based centralized management

- Managed centrally over the web
- Classifies applications, users and devices
- Zero-touch, self-provisioning deployments

Networking and security

- Stateful firewall
- Auto VPN™ self-configuring site-to-site VPN
- Active Directory integration
- Identity-based policies
- Client VPN (IPsec)
- 3G / 4G failover via USB modem

Traffic shaping and application management

- Layer 7 application visibility and traffic shaping
- Application prioritization

MX-64

→ Network and Security Services

- Stateful firewall, 1:1 NAT, DHCP, DMZ, static routing
- Identity-based policies
- Auto VPN™ self-configuring site-to-site VPN
- Client VPN (IPsec)
- User and device quarantine
- VLAN support and DHCP services

→ Advanced Security Services

- Content filtering (Webroot BrightCloud CIPA-compliant URL database)
- Web search filtering (including Google and Bing SafeSearch)
- YouTube for Schools
- Intrusion prevention (SourceFire Snort based)
- Antivirus and antiphishing filtering (Kaspersky SafeStream II engine)
- Requires Advanced Security License

→ WAN Performance Management

- WAN link aggregation
- Application level (Layer 7) traffic analysis and shaping
- Automatic Layer 3 failover (including VPN connections)
- WAN uplink selection based on traffic type

→ Monitoring and Management

- Web based management and configuration
- Throughput, connectivity monitoring and alerts
- Network asset discovery and user identification
- Built-in network-wide reporting, monitoring and alerts
- Centralized policy management
- Real-time diagnostic and troubleshooting over the web
- Automatic firmware upgrades and security patches
- Searchable network-wide event logs

→ Interfaces

- WAN: 1 × 1 GbE
- LAN: 4 × 1 GbE (1 optionally available for WAN connectivity)
- USB: 1 × USB 2.0 for 3G/4G failover (supported devices)

→ Performance

- Stateful firewall throughput: 250 Mbps
- VPN throughput: 100 Mbps
- Recommended for small branches (up to 50 users)

→ Power

- Single 18W power supply

→ Environment

- Operating temperature: 32°F to 104°F (0°C to 40°C)
- Humidity: 5 to 95% non-condensing

Communication Service Solutions

Sales: 1-866-727-4300

Tel. 580-548-1605

sales@comservicesolutions.com

www.comservicesolutions.com